



## PLUSTEK OPTICFILM 7200 (SCANNER FILM)

*Scanner film, 7200 dpi, 35 mm, USB 2.0*

Scannerul OpticFilm 7200 are o rezolutie de 7200 dpi, fiind capabil de a scana slide-uri si negative de 35mm. Rezolutia foarte mare, conectarea USB 2.0 si viteza mare de scanare permit acestui film scanner sa concureze de la egal la egal cu multe alte scannere profesionale foarte costisitoare.



Before

After



### EUROCOM S.A.

Distribuitor Océ, ZyLab si PlusTek in Romania  
 Union International Center, etaj 6, Str. Ion. Campineanu 11, Sector 1, Bucuresti  
 Tel: (021) 311.29.70; 311.30.26; 311.13.74

Pagina 1 din 2

Fax: (021) 312.76.74

[www.eurocom.ro](http://www.eurocom.ro)



<b>Interfata</b>	USB 2.0 Full Speed
<b>Tehnologie</b>	Color CCD
<b>Rezolutie</b>	7200 x 7200 dpi
<b>Dmax</b>	3.3
<b>Zona maxima de scanare</b>	36.8 x 25.4 mm (1.45 "x 1") *
<b>Viteza previzualizare</b>	Aprox. 5.6 sec **
<b>Viteza de scanare</b>	Aprox. 36 sec (3600 dpi), 68 sec (7200 dpi) ***
<b>Adancimea de culoare</b>	48 biti/pixel
<b>Dimensiuni (D x W x H)</b>	272 x 120 x 119 mm (doar scanner-ul)
<b>Greutate neta</b>	Aprox. 1.5 kg (doar scanner-ul)
<b>Mod scanare</b>	Single Pass (o singura trecere)
<b>Tip lampa</b>	Cold cathode
<b>Film holder</b>	Pana la 4 slide-uri montate si filmstrips cu pana la 6 frame-uri
<b>Certificate conformitate</b>	CE, FCC, UL/cUL, TUV
<b>Software</b>	SilverFast Ai iSRD
<b>Cerinte de sistem</b>	PC compatibil IBM, procesor Pentium II sau mai rapid
	CD-ROM
	Un port USB disponibil
	128 MB RAM (256 MB recomandat)
	160 MB spatiu liber pe HDD (300 MB recomandat)
	Placa video High Color (VGA sau mai bun)
	Microsoft Windows XP, Me, 98 SE, 2000

\* Negativ

\*\* Negativ, timpul de calibrare nu este inclus

\*\*\* Negativ in modul True Colour (24 biti), timpul de calibrare nu este inclus