



OPTICSLIM 2420T

Compact size, unsurpassed image quality, and high-performance are some of the features that the OpticSlim 2420T has to offer. With optical resolution of 1200 dpi and 48-bit output colour, your work is sharp and vivid. The OpticSlim 2420T is power adaptor free using the USB connection.

- **Forma ultra slim**, numai 3.3 cm in inaltime. Usor de depozitat cand nu este folosit.
- Echipat cu un adaptor de transparente fara cablu numit **UFO Lite**. OpticSlim 2420T poate scana de asemenea diafilme pozitive si negative cu suporturi speciale de film.
- **5 butoane one-touch action**, Copy, OCR, E-Mail, Custom si Scan (Functia butonului Custom poate fi setata folosind Action Manager.)
- Conexiune USB 2.0
- Fara cablu de alimentare

Interfata	USB 2.0
Tehnologie	Advanced Color CIS (Contact Image Sensor)
Rezolutie Hardware	1200 x 2400 dpi
Rezolutie interpolata	24000 dpi
Moduri de scanare	Color: 48-bit input, 24/48-bit output Grayscale: 16-bit input, 8/16-bit output B/W: 1-bit
Zona Max. scanare	216 x 297 mm (8.5" x 11.69", A4/ Letter Size)
Greutate neta	Approx. 1400g / 3.1 lbs (scanner only)
Dimensiuni (D x W x H)	378 x 257 x 33 mm (scanner only)
Mod de scanare	Single Pass
Lungimea cablului	150 cm (59.06")
Certificari	CE, FCC, UL/cUL, TUV
UFO Lite Specification	
Scanning Area	23.6 x 35 mm (0.93" x 1.38")
Net Weigh	62 g / 2.2 oz
W x D x H (mm / inch)	102 x 67 x 24 mm / 4" x 2.6" x 0.95"
Cerintele sistemului	PC compatibil IBM , cu Pentium II sau CPU mai rapid CD-ROM Drive Un port USB disponibil 64MB RAM (128MB recomandat) 160 MB spatiu HDD (260 MB recomandat) Placa video (VGA sau mai performant) Microsoft Windows XP, Me, 98, 2000

