


# imageRUNNER C1225iF

## Productive and cost effective A4 colour multifunctional

The imageRUNNER C1225iF is a feature rich A4 colour multifunctional device, providing fast and efficient document handling 'out of the box' so you can focus on your business priorities.



- Powerful A4 colour multifunctional with print, copy, colour scan, send and fax functionality, ideal for demanding small businesses
- Simple and user friendly operation with the 8.9 cm colour touch and swipe LCD display
- Canon's V<sup>2</sup> colour (Vivid and Vibrant) imaging technology ensures documents impress and stand out from the rest
- Seamlessly fits into your office environment with network connectivity and supporting IT standards such as PCL and Genuine Adobe PS
- Increase productivity with up to 1,100 sheet capacity and a Duplex Automatic Document Feeder (DADF)
- Scan and Send documents directly to a variety of destinations including email and shared folder
- Flexible mobile printing and scanning capabilities such as Apple AirPrint™, Mopria printing as well as mobile printing and scanning apps, support mobile worker efficiency
- Out of the box easy install; users can access the set-up guide via the user interface
- Consumables can be changed easily reducing down-time
- Standard toner included in the box giving up to 12 months colour printing<sup>1</sup>
- Giving you peace of mind with Canon's standard warranty
- Energy consumption as little as 1 watt in sleep mode
- Compact and efficient space saving design



PRINT



COPY



FAX



SCAN

AirPrint™ and the AirPrint logo are trademarks of Apple Inc.  
<sup>1</sup>Actual results will vary and may be higher or lower than 12 months depending on individual usage. 12 months colour printing is based on a monthly print volume of 1,000 pages, 30% colour pages and 5% A4 coverage (ISO/IEC 24712). Standard Black toner yield is 12,000 pages. Yellow, Magenta and Cyan toner yield is 7,300 pages

# Technical Specifications

# imageRUNNER C1225iF

<b>Machine type</b>	Colour A4 Laser Multifunctional (Reader / Printer standard)	<b>Scan resolution</b>	<b>BW Scan:</b> 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi <b>CL Scan:</b> 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi
<b>Available core functions</b>	Print, Copy, Scan, Send and Fax standard for C1225iF	<b>Double sided scanning</b>	2-sided to 2-sided (Automatic)
<b>Printer Specifications</b>		<b>Scan speed</b>	BW single-sided: 25 ipm (A4, 300 dpi X 300 dpi), BW double-sided: 9 ipm (A4, 300 dpi X 300 dpi) CL single-sided: 25 ipm (A4, 300 dpi X 300 dpi), CL double-sided: 9 ipm (A4, 300 dpi X 300 dpi)
<b>Print speed (BW/Colour)</b>	25/25ppm (A4 Single-sided), 26/26ppm (A5 Single-sided), 25/25ppm (A4 Double-sided), 26/26ppm (A5 Double-sided)	<b>Scan methods</b>	Push Scan: Colour Send functionality is standard. Pull Scan: TWAIN/WIA Pull scanning available on all models. Scan to USB Memory Key: Available on all models Scan to mobiles, internet-connected devices: A range of solutions is available to provide scanning to mobile devices, internet-connected devices depending on your requirements. Please contact your sales representative for further information.
<b>Printing method</b>	Colour Laser Beam Printing	<b>Pull scan specifications</b>	<u>TWAIN/WIA Pull scanning</u> Windows XP Windows Vista/Windows 7/Windows 8/Windows 8.1 <u>Mac Scan (TWAIN only)</u> Mac OS X 10.5.8 or later *The drivers are available via <a href="http://software.canon-europe.com">http://software.canon-europe.com</a> .
<b>Print resolution</b>	2400 dpi equivalent x 600 dpi, 600 dpi x 600 dpi	<b>Send Specifications</b>	Standard on all models
<b>Double sided printing</b>	Automatic (Standard)	<b>Optional/Standard</b>	100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi
<b>Direct print</b>	Direct printing available from USB memory key Supported file types: JPEG, TIFF, PDF	<b>Send resolution</b>	E-Mail, Fax (not available for C1225), PC (SMB, FTP)
<b>Printing from mobiles or internet-connected devices and cloud-based services</b>	A range of software is available to provide printing from mobile or internet-connected devices. Please contact your sales representative for further information.	<b>Destinations</b>	LDAP (Max. 50 searchable), Local (Max. 300 including 281 Speed dials)
<b>Paper input (Standard)</b>	1 x 550-sheet (80 gsm) cassette, 100-sheet (80 gsm) multi-purpose tray	<b>Address Book/Speed dials</b>	SMB : JPEG, TIFF, PDF, Compact PDF, Searchable PDF E-mail : PDF, Compact PDF, Searchable PDF
<b>Paper input (Option)</b>	1 x 550-sheet cassette (80 gsm) (Cassette Feeding Unit-AJ1)	<b>File formats</b>	Send PDF Security Feature Set-E1@E: Send encrypted PDF and add digital device signature to PDF files.
<b>Maximum paper input capacity</b>	1200 sheets (80 gsm)	<b>Optional Universal Send Feature Sets</b>	
<b>Paper output capacity</b>	250 sheets (80 gsm)	<b>Fax Specifications</b>	Standard for C1225iF
<b>Finishing capabilities</b>	Standard: Collate, Group	<b>Optional/Standard</b>	Super G3 33.6 kbps (Up to 3 seconds per page*)
<b>Supported media types</b>	<u>Cassette/s:</u> Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Envelopes* *Envelope support via standard cassette 1 only. <u>Multi-purpose tray:</u> Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Transparency, Labels, Envelopes (No.10 (COM10), Monarch, ISO-C5, DL)	<b>Modem speed</b>	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi
<b>Supported media sizes</b>	<u>Paper cassette 1:</u> Standard size: A4, A5, B5, Legal, Letter, Executive, Statement, Envelopes (No.10 (COM10), Monarch, DL) Custom size (98.4 mm to 216 mm X 190.5 mm to 355.6 mm) <u>Paper cassettes 2:</u> Standard size: A4, A5, B5, Legal, Letter, Executive, Statement Custom size (98.4 mm to 216 mm X 190.5 mm to 355.6 mm) <u>Multi-purpose tray:</u> Standard size: A4, A5, B5, Legal, Letter, Executive, Statement, Custom size (98.4 mm to 216 mm x 148 mm to 355.6 mm), Envelopes (No.10 (COM10), Monarch, ISO-C5,DL)	<b>Fax resolution</b>	Up to 512 pages <sup>1</sup> Max. 281 Max. 199 dials Max. 310 addresses Yes Fax Forwarding, Dual Access, PC Fax (TX only)
<b>Supported media weights</b>	<u>Cassette/s :</u> 60 to 163 gsm Multi-purpose tray: 60 to 220 gsm Duplex: 60 to 163 gsm	<b>Fax memory</b>	
<b>Page Description Language(s)</b>	UFRII , PCL5c/6, Adobe PostScript Level 3 (Standard for C1225iF)	<b>Speed dials</b>	
<b>Fonts</b>	PCL fonts: 93 Roman, 10 Bitmap, 2 OCR fonts PS fonts: 136 Roman fonts	<b>Group dials / destinations</b>	
<b>Operating System compatibility</b>	UFRII: Windows XP / Server 2003 / Vista / Server 2008 / Windows 7 / Server 2008R2 / Windows 8 / Windows 8.1 / Server 2012 / Server 2012R2, MAC OS X (10.5.8 or later) PCL: Windows XP / Server 2003 / Vista / Server 2008 / Windows 7 / Server 2008 R2 / Windows 8 / Windows 8.1 / Server 2012 / Server 2012R2 PS: Windows XP / Server 2003 / Vista / Server 2008 / Windows 7 / Server 2008 R2 / Windows 8/Windows 8.1 / Server 2012 / Server 2012R2, MAC OS X (10.5.8 or later) PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows XP / Windows Vista / Windows 7 / Windows 8/ Windows 8.1 Please refer to <a href="http://software.canon-europe.com/">http://software.canon-europe.com/</a> for availability of print solutions for other operating systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place.	<b>Sequential broadcast</b>	
<b>Copy Specifications</b>		<b>Memory backup</b>	Yes
<b>Copy speed (BW/Colour)</b>	Please refer to the quoted print speeds	<b>Other features</b>	
<b>First Copy Output Time (FCOT) (BW/Colour)</b>	8.4 sec / 10.5 sec	<b>General Specifications</b>	
<b>Copy resolution</b>	Reading: 600 dpi x 600 dpi Printing: 600 dpi x 600 dpi	<b>Warm-up time</b>	Approx. 34 seconds from power ON
<b>Multiple copy Reduction/Enlargement</b>	Up to 999 copies Zoom: 25 - 400 % in 1 % increments Fixed Zoom Ratio: 25%, 50%, 70%, 100%, 141%, 200%, 400%	<b>Recovery from sleep mode</b>	10 seconds or less
<b>Scan Specifications</b>		<b>Interface type</b>	USB 2.0 Hi-Speed/1000BaseT / 100Base-TX / 10Base-T, 1 x USB Host (Front), 1 x USB Host (Rear), 1 x USB device Recommended third party wireless solution is Silex SX-BR-4600 WAN. For more details please refer to <a href="http://www.silex-europe.com">www.silex-europe.com</a> TCP/IP* (LPD / Port 9100 / WSD / IPP / IPPS / SMB / FTP), IPX/SPX (NDS, Bindery) *IPv4/IPv6 support
<b>Optional/Standard</b>	Standard on all models (DADF 50 sheets)	<b>Network protocols</b>	1.0 GB
<b>Supported media size/s</b>	A4, A5, B5, Custom sizes: 140 mm to 216 mm x 128 mm to 356 mm (when fed through the DADF)	<b>Memory</b>	QVGA Color LCD 8.9 cm (3.5 inch) touch / swipe supported display
<b>Supported media weight/s</b>	Single-sided scanning: 50 to 105 gsm (DADF) Double-sided scanning: 64 to 105 gsm (DADF)	<b>Control panel</b>	Standard: 511 mm x 549 mm x 610 mm Optional: With Cassette Feeding Unit-AJ1: 511 mm x 549 mm x 1035 mm
		<b>Dimensions (W x D x H)</b>	852 mm x 843 mm (Main unit + Multi-purpose tray open + Cassette drawers open)
		<b>Installation space (W x D)</b>	Approx. 44 kg including toner
		<b>Weight</b>	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80 % RH (no condensation)
		<b>Operating environment</b>	220 - 240 V (±10 %), 50/60 Hz (±2 Hz), 3.7 Amp
		<b>Power source</b>	Maximum: Approx. 1.5 KW Standby: Approx. 30 W Sleep mode: Approx. 1.0 W or less <sup>2</sup> Time to put the device to sleep mode : 60 sec Typical Electricity Consumption (TEC) rating <sup>3</sup> : 0.8 kWh
		<b>Power consumption</b>	Only for C1225 (non Fax model) Plugin-off: 0.5W or less (Normal mode) Time to put the device to plugin-off: 4 hours

# Technical Specifications

# imageRUNNER C1225iF

**Noise levels**  
**Sound Pressure** <sup>4</sup>  
 (reference data, LpAm,  
 Bystander's position)  
**Software and printer  
 management**

Sound Pressure Noise Levels:  
 Active: 50 dB  
 Standby: Inaudible (Less than 30dB)

**eMaintenance:** embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.

**Remote Firmware System (GDLS):**

Allows the remote distribution of firmware.

**Remote User Interface (RUI):** Web-based interface to each device that helps to provide remote device management and control.

**Canon Driver Configuration Tool:** A utility for changing the factory default settings of Canon print drivers

Standard:  
 IP/Mac Address Filtering, IPSEC, SNMP V3.0, IEEE 802.1X, Secured Print, Department ID  
 Optional: Send PDF Security Feature Set-E1@E

Toner 34 Black / Cyan / Magenta / Yellow Toner  
 (Yield: BK 12,000 / CMY 7,300 pages) <sup>5</sup>

**Security features**

**Consumables**

**Toner bottle**

## Specifications for options

### Cassette feeding unit

Name: Cassette Feeding Unit-AJ1  
 Description: Optional cassette feeding unit with 1 x 550 sheets paper capacity. Takes the cassette paper capacity up to 1,200 sheets.  
 Dimensions (W x D x H): 511 mm x 508 mm x 425 mm  
 Weight: Approx. 15 kg

HANDSET-J1 EUR/HANDSET-J1 SA

BARCODE PRINTING KIT-D1@E: Enables barcode printing via jet caps technology.

Send PDF Security Feature Set-E1@E: Send encrypted PDF and add digital device signature to PDF files.

Drum Unit 034 (BK / C / M / Y)

Waste Toner Box WT-A3:

### Hardware accessories 1

### Print controller accessories

### Document security accessories

### Other options

### Footnotes

<sup>1</sup>Based on ITU-T Standard Chart No. 1

<sup>2</sup>1 watt sleep mode may not be possible in all circumstances. Certain network configurations and options may prevent the device from entering deep sleep mode. Please refer to the user guide for more information

<sup>3</sup>Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh). The test methodology is defined by Energy Star (<http://www.eu-energystar.org>).

<sup>4</sup>Declared noise emission in accordance with ISO 7779

<sup>5</sup>Based on 5% coverage (A4)

All specifications subject to change without notice



SAP® Printer Vendor Solution



Canon Inc.  
 canon.com

Canon Europe  
 canon-europe.com

UK English edition  
 © Canon Europa N.V., 2015

Canon (UK) Ltd  
 Woodhatch  
 Reigate  
 Surrey RH2 8BF  
 Telephone no 01737 220000  
 Facsimile 01737 220022  
 canon.co.uk

Canon Ireland  
 3006 Lake Drive  
 Citywest, Saggart  
 Co.Dublin, Ireland  
 Telephone No: 01 2052400  
 Facsimile No: 01 2052525  
 canon.ie

