

Océ VarioPrint[®] 6000 Ultra Line

Experience ultra speed

Ready to take your cutsheet printing performance to new heights? Meet the Océ VarioPrint 6000 Ultra Line, the world's fastest and most productive family of digital perfecting printing systems. Choose from four models: Océ VarioPrint 6320 Ultra, Océ VarioPrint 6250 Ultra, Océ VarioPrint 6200 Ultra and Océ VarioPrint 6160 Ultra. All are based on Océ Gemini Instant Duplex technology for unmatched power and scalability at speeds of 170, 200, 250 or a blazing 314 duplex images per minute.



General

- Océ Gemini technology for instant duplex printing
- Advanced Active Registration technology
- Sophisticated media handling from up to 12 paper trays
- Océ Paper Logic technology for fast and easy paper orientation
- Increased throughput to handle more business
- Scalability and flexibility for protection of investment
- Handle the diverse challenges of book printing, transactional and reprographic jobs with a single solution

Various configurations

In today's environment, people all have their own demands. That's why the Océ VarioPrint 6320, 6250, 6200 and 6160 Ultra are available in various configurations to fit perfectly with individual needs and wishes. You can choose which combination of modules fits your needs.

User interface

- Intuitive 15" colour touchscreen user interface
- Multiple views ensure a productive and controlled workflow
- Access to features and functions: Queue manager, Job scheduler, system status overview, multiple queues, job selection options, bundle printing

Océ VarioPrint 6000 Ultra Line Digital perfecting systems for ultra high speed

Finishing

Many finishing options are available, including:

- Booklet making
- Tape binding
- Perfect binding
- Punching
- Folding

Configurations

Many combinations of modules are available, including:

- 1 Paper input module
- 2 Océ Gemini Instant Duplex engine
- 3 High capacity stacker
- 4 Set finisher







Technology		Optional Roll feeder	
Imaging technology	Océ Gemini technology for instant duplex printing,	Supplier	Hunkeler or Lasemax Roll Systems roll feeders
	Advanced Active Registration technology, Paper Logic		·
Resolution	0 0, 1 0	Note	Can be combined with one or two paper input modules
	LED, 600 x 1200 dpi, 85/106/125/141/180 lpi	Input interface module	
Print speed		Dimensions (WxDxH)	470 x 1060 x 1150 mm
VarioPrint 6320 Ultra	A4: 314 images	Weight	100 kg
	A3: 168 images	High capacity stacker	8
VarioPrint 6250 Ultra	A4: 250 images	Description	Three high capacity stackers can be included
	A3: 132 images		
VarioPrint 6200 Ultra	A4: 200 images	Paper trays	2 x 3000 sheets (80 gsm) per stacker
	A3: 106 images	Paper size	203 x 203 mm - 320 x 488 mm (8" x 8" - 12.6" x 19.2")
VarioPrint 6160 Ultra	A4: 170 images	Maximum paper	18,000 sheets (3 stackers)
	A3: 88 images	capacity	
Note	. 0	Dimensions (WxDxH)	1154 x 850 x 1150 mm
Recommended monthly	print volume		1154 x 850 x 1928 mm (including integrated
Océ VarioPrint 6320			multi-format stapler)
Ultra	1,000,000 - 10,000,000 (images A4)	Weight	178 kg (290 kg including integrated multi-format stapler)
Océ VarioPrint 6250	750,000 - 8,000,000 (images A4)	Features	Tab printing, interface to third-party finishing
Ultra	/ 30,000 - 0,000,000 (mages 114)	Option	PowerLift for lifting and moving paper stacks
Océ VarioPrint 6200	500,000 - 5,000,000 (images A4)		r owerEnt for inting and moving paper stacks
Ultra)00,000),000,000 (mingeo 114)	Set finisher	
Océ VarioPrint 6160	300,000 - 2,500,000 (images A4)	Output capacity	3500 stapled sheets (80 gsm, A4)
Ultra	5 7 7 7 7 8 0	Maximum stapling	100 sheets (80 gsm)
General		capacity	
Operation	Intuitive 15 inch colour touchscreen	Paper size	208 x 275 mm - 220 x 306 mm (8.2" x 10.8" - 8.7" x
Dimensions main			12")
engine (WxDxH)	1443 x 1070 x 1204 mm	Features	Corner stapling, Two-point stapling (Portrait, Landscape,
Weight main engine	760 kg		Book)
	/		Option: short 50-sheet staples
Environmental		Finishing options	
Sound power level	Standby mode: 58 dB		Booklet making, Tape binding, Perfect binding,
	Print mode: 78 dB		Punching, Folding
Power consumption,	1 kW	Controller	
Standby mode		Interface	Ethernet (10/100/1000 Base T)
Power consumption,	VarioPrint 6160 Ultra: 4.0 kW		Ethernet $(10/100/1000 \text{ Base-T})$
Print mode	VarioPrint 6200 Ultra: 4.3 kW	Page Description Language	Adobe [®] PostScript [®] 3 (standard), PDF, PCL 5e / PJL,
	VarioPrint 6250 Ultra: 4.4 kW		PCL 6, IPDS
	VarioPrint 6320 Ultra: 4.9 kW	Protocols	TCP/IP, IPP, SMB, LPR / LPD, Socket printing, SNMP
Paper handling			(MIB II, Printer MIB, Job monitoring MIB)
Paper input	Standard: Paper input module with four paper trays	Workflow	
	Options: second and third paper input modules	Features	Automatic language sensing (PostScript, PDF and PCL
Maximum paper	13,800 sheets from 12 standard and optional paper trays		6)
capacity	(80 gsm)		Instant switching from IPDS or PCL5e /PJL to PostScript
Paper weight	50 - 300 gsm on Océ approved media: 60 - 200 gsm on		3, PDF or PCL 6
·	50 - 300 gsm on Océ approved media; 60 - 200 gsm on other media		Streaming behaviour for all PDLs
Paper size			Xerox [®] DigiPath [®] / FreeFlow software and job ticket
raper size	203 x 203 mm - 320 x 488 mm (8" x 8" - 12.6" x 19.2"); Statement (178 x 252 mm, 7" x 10")		support with Océ DPlink software
Standard manay types	Statement (1/6 x 2)2 mm, / x 10)		Kodak [®] SmartBoard [®] connectivity support with Océ
Standard paper trays			KDKlink
Paper trays	2 x 600 sheets; 2 x 1700 sheets (80 gsm)	Software	
Maximum paper	4600 sheets		Océ PRISMA®access, Océ PRISMAprepare, Océ PRISMAproduction, Océ PRISMAsatellite for ERP, Océ
capacity			PRISMAproduction, Océ PRISMAsatellite for ERP, Océ
Dimensions (WxDxH)	940 x 716 x 1150 mm		Document Designer Advanced, Océ PRISMAspool, Océ
Weight	180 kg		Dpconvert, Océ VPconvert, Océ MeterManager
Additional paper trays	0		
Description	Apart from the standard paper input module, two extra		
Doorption	paper input modules can be included		
Paper trave			
Paper trays	2 x 600 sheets and 2 x 1700 sheets (80 gsm) per paper input module		
Maximum	1		
Maximum paper capacity	9200 sheets (for two paper input modules)		
Paper size	203 x 203 mm - 320 x 488 mm (8" x 8" - 12.6" x 19.2");		
1 apor 0120	Statement $(178 \times 252 \text{ mm}, 7" \times 10")$		
Paper size ention			
Paper size option	350 x 500 mm (13.8" x 19.7") in all trays		
Dimensions (WxDxH)	940 x 716 x 1150 mm		
Weight	180 kg		
	·		

Beyond the Ordinary





Creating global leadership in printing

Canon and Océ have joined forces to create the global leader in the printing industries. Our customers can choose from one of the industry's broadest range of products backed by best-in-class service and support organisations. Look to the new Canon-Océ combination for:

- Enterprise printing in the office and corporate printroom
- Large format printing of technical documentation, signage and display graphics
- Production printing for marketing service bureaus and graphic arts
- Business Services for document process outsourcing

© 2012 Océ

Illustrations and specifications do not necessarily apply to products and services offered in each local market. Technical specifications are subject to change without prior notice.

Océ, Océ VarioPrint, Océ Paper Logic and Océ PRISMA software are registered trademarks of Océ-Technologies B.V. Xerox DigiPath and Kodak SmartBoard are registered trademark of Xerox Corporation and Kodak. PostScript is a registered trademark of Adobe Systems Incorporated. All other trademarks are the property of their respective owners.

For information and services, visit us at:

www.oce.com

Edition 2012-08

GB