

imageRUNNER ADVANCE 8085 PRO 8095 PRO 8105 PRO

Explore your
production potential.

you can

Leap into the next generation with our most advanced mono Light Production printers. A brilliant blend of high-end finishing, powerful workflow integration and ease of use, the imageRUNNER ADVANCE 8000 PRO series makes light work of the most heavyweight production tasks.

85 - 105 PPM PPM MONO MONO
1200DPI PRINTING
LARGE PAPER CAPACITY
SADDLE STITCHING & TRIMMING
MODULAR DESIGN
POWERFUL WORKFLOW INTEGRATION



Productivity

- Up to 105 ppm mono printing
- Extensive paper capacity with up to 6 different sources
- Load and replenish toner during printing
- Media up to 256g/m²
- Choice of Canon or Fiery-based RIPs
- Powerful workflow integration
- Large touch screen with intuitive operation

Professional Finishing

- Extensive capabilities – Professional punching, folding, inserting, and saddle stitching with trimming

Versatility

- Easy integration
- Modular design enables multiple configurations
- Mixed media with weights up to 256g/m²

Environment

- Lowest TEC rating (Typical Electricity Consumption) in class
- Incorporates recycled and bio-plastics
- Less than 1 minute warm-up time

Quality

- Up to 1200dpi printing
- Excellent text / dot reproduction
- Accurate half-tone density

 **imageRUNNER**
ADVANCE

Canon

Specifications: imageRUNNER ADVANCE 8085 PRO/ 8095 PRO/ 8105 PRO

Type	Console			
Maximum Original Size	A3			
Copy Sizes	Cassettes 1 & 2	A4		
	Cassettes 3 & 4	ASR - 330 x 483 mm, Free size 139.7 x 182 mm to 330.2 x 487.7 mm		
Stack bypass	ASR - 330 x 483 mm			
	Free size 100 x 148 mm to 330.2 x 487.7 mm			
Resolution	Reading	600 dpi x 600 dpi		
	Copying	1200 dpi x 1200 dpi		
	Printing	1200 dpi x 1200 dpi		
	256 gradations			
Copy/Print Speed	A4	A3	SRA3	
	iR-ADV 8105 PRO	105	54	50.4
	iR-ADV 8095 PRO	95	50	45.6
	iR-ADV 8085 PRO	85	44	40.8
Enlargement / Reduction	Zoom	2.5-400%		
	Fixed	2.5-400% (25%, 50%, 71%, 100%, 141%, 200%, 400%)		
First copy time	2.7 sec or less			
Warm-Up Time	less than 1 minute			
Multiple Copies/Prints	1 to 9,999 sheets			
Duplexing	Standard automatic stackless			
Paper weight	Cassette: 52 to 220 g/m ² , Stack Bypass: 52 to 256 g/m ²			
Paper capacity	Duplex: 52 to 220 g/m ²	Standard		
		1,500 sheets x 2 cassettes (80 g/m ²)	550 sheets x 2 cassettes (80 g/m ²)	
Processor Speed	Total capacity	7,700 sheets (with optional paper decks)		
	Memory	1.2 GHz		
Hard Disk Drive	1.5 GB			
Display	Standard 80 GB, expandable to 250 GB			
Interface	10.4" TFT SVGA touchscreen			
	Ethernet (1000Base-T/100Base-TX/10Base-T), Wireless LAN (IEEE802.11b/g, Optional), USB2.0			
Network Protocols	TCP/IP* (LPD/Port9100/WSD/IPP/PPS/SMB/FTP), IPX/SPX (NDS, Bindery), AppleTalk. *IPv4/IPv6 support			
	220-240V AC, 50/60Hz 10A			
Power Supply	2.4 kW max.			
Power Consumption	1,170 x 770 x 1,252 mm (including Duplex Color Image Reader Unit-C1 & control panel)			
Dimensions (WxDxH)	242 kg (with Duplex Color Image Reader Unit-C1)			
Weight				
PRINTING				
Page Description Language(s)	UFRII (Standard on all models), PCL5e/6 (Optional with Canon PCL Printer Kit-AH1), Adobe PostScript 3 (Optional with Canon PS Printer kit-AH1)			
Resolution	1200 dpi x 1200 dpi, 600 dpi x 600 dpi			
Fonts	PCL fonts: Roman93, Bitmap10, OCR2, PS fonts: Roman136			
Supported OS	UFRII, PCL & PS3: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2 UFRII & PS3 also supports Mac OS X (10.4.9 or later) Mac-PPD: Mac OS 9.1 or later, Mac OS X (10.2.8 or later)			
FIERY-BASED PRINTING				
Name	imagePASS-U1 (optional)			
PDL	Adobe PostScript 3, PCL6 / PCL5e			
Resolution	1200 dpi x 1200 dpi, 600 dpi x 600 dpi			
Memory	2G B			
Hard Disk	80 GB			
CPU	Intel Core Duo T2500, 2.0 GHz,			
Fonts	PS: 136, PCL: 113			
Supported OS	Windows 2000 SP4 (Printer driver only)/XP (SP3)/Server2003 (SP2)/ Server2008 (SP2)/Vista (SP2), Windows 7, Mac OS X 10.4 or later			
Interface	Ethernet 1000Base-T/100Base-TX/10Base-T, USB, D-sub 15-pin connector			
Network Protocol	TCP/IP (LPD/Port9100/PPS/SMB/FTP), ATP/DDP (AppleTalk)			
DOCUMENT FEEDER				
Colour Image Reader Name	Duplex Color Image Reader Unit-C1 (optional)			
Paper size	A3, A4, A4R, A5, A5R			
Paper weight	Single Sided Original: 38 to 220 g/m ² Double Sided Original: 50 to 220 g/m ² Colour Original: 64 to 220 g/m ²			
Max. Number of originals	300 sheets (80 g/m ²)			
Scanning speed (max.)	Copy (Single side): A4 120 ipm 600 dpi (B&W), Scan (Single side): A4 120 ipm 300 dpi (B&W), 85 ipm 300 dpi (Colour), Copy (Double side): A4 120 ipm 600 dpi (B&W), Scan (Double side): A4 200 ipm 300 dpi (B&W), 100 ipm 300 dpi (Colour)			
Dimensions (WxDxH)	635 x 605 x 253 mm			
Weight	Approx. 39.4 kg			
PAPER DECK UNIT-C1				
Paper size	A4			
Paper weight	52 to 220 g/m ²			
Paper capacity	3,500 sheets (80 g/m ²)			
Dimensions (W x D x H)	323 x 583 x 570 mm			
Weight	Approx. 37 kg			
Staple Finisher-F1 PRO				
Booklet Finisher-F1 PRO				
Number of trays	2 trays			
Tray capacity (Non Collate)	Tray A: A4/A4R/A5R 3,000 sheets, A3 1,500 sheets, SRA3/13"x19" 1,000 sheets Tray B: A4/A4R 2,000 sheets, A3 1,000 sheets			
Staple position	Corner - Double - Booklet (Booklet Finisher only)			
Staple capacity (80gsm)	A4: 100 sheets, A3/A4R: 50 sheets			
Booklet stitch paper size (booklet finisher only)	A3, A4R, SRA3, 13"x19"			
Booklet stitch staple capacity	Free size 210x279mm to 330.2x487.7mm 25 sheets (80g/m ²) (booklet finisher only)			
Dimensions	Staple Finisher 800 x 792 x 1180mm Booklet Finisher 800 x 792 x 1180mm			
Weight	Staple Finisher Approx. 130kg Booklet Finisher Approx. 180kg			

Staple Finisher-D1	Number of trays	3 trays			
Booklet Finisher-D1	Tray capacity:	Tray A Capacity: A4/A5R 1,500 sheets, A3/A4R/SRA3/13"x19" 750 sheets Tray B Capacity: A4/A5R 250 sheets, A3/A4R 125 sheets, SRA3/13"x19" 30 sheets Tray C Capacity: A4 2,500 sheets, ASR 1,500 sheets, A3/A4R/SRA3/13"x19" 750 sheets			
	Staple position	Corner - Double - Booklet (Booklet Finisher only)			
	Staple capacity (80gsm)	A4: 100 sheets, A3/A4R: 50 sheets			
	Booklet stitch paper size	A3, A4R, SRA3, 13"x19" (booklet finisher only)			
	Booklet stitch staple capacity	20 sheets (80g/m ²) (booklet finisher only)			
	Dimensions	Staple Finisher 782 x 765 x 1040mm Booklet Finisher 896 x 765 x 1040mm			
	Weight	Staple Finisher Approx. 61kg Booklet Finisher Approx. 108kg			
Booklet Trimmer-D1	(requires Booklet Finisher-F1 PRO)				
Inner Booklet Trimmer-A1	(requires Booklet Finisher-D1)				
	Trim Width	One Edge Trimming (Fore-edge) 2-20mm			
	Trim Thickness	Up to 25 sheets (includes Cover)			
	Acceptable Paper Weight	Up to 20 sheets (includes Cover) 60 to 256g/m ²			
	Weight	Inner Booklet Trimmer-A1 Approx. 32kg Booklet Trimmer-D1 Approx. 152kg			
DOCUMENT INSERTION UNIT-K1	Number of trays	2			
	Paper Size	A3, A4, A4R, SRA3, 13" x 19", Free size (182 x 182 mm to 330.2 x 487.7 mm)			
	Paper Weight	52 to 256 g/m ²			
	Paper Capacity	200 sheets x 2 tray (80 g/m ²)			
	Dimensions (W x D x H)	746 x 793 x 1,407 mm			
	Weight	Approx. 61 kg			
PAPER FOLDING UNIT-H1	Z-Fold	Paper Size	A3, A4R	Paper Weight	52 to 105 g/m ²
	C-Fold	Paper Size	A4R	Paper Weight	52 to 105 g/m ²
	Letter fold out	Paper Size	A4R	Paper Weight	52 to 105 g/m ²
	Double Parallel	Paper Size	A4R	Paper Weight	52 to 90 g/m ²
	Half Fold	Paper Size	A4R	Paper Weight	52 to 105 g/m ²
	Output Capacity	C-Fold and Letter fold out: 40 sheets Double parallel: 25 sheets			
	Dimensions (W x D x H)	336 x 793 x 1,190 mm			
	Weight	Approx. 71 kg			
PROFESSIONAL PUNCHER-C1	External In-line Punch Unit (requires Professional puncher integration unit-B1)				
Acceptable Punch Paper Weight	75-216 g/m ² (Plain paper)				
Acceptable Punch Paper Size	A4				
Punch tools	Plastic Comb 21-Hole, Twin Loop 23-Hole (Round), Twin Loop 34-Hole (Round), Color Coil 47-Hole, Velo Bind 12-Hole, Loose Leaf 4-Hole Punch, Loose Leaf 2-Hole Punch, Loose Leaf 4-Hole (Swedish) Pro Click 34-Hole				
Dimensions (W x D x H)	305 x 792 x 1,040 mm				
Weight	Approx. 80 kg				
Additional Options	Printer Cover-B1, Stamp Ink Cartridge-C1, ADF Access Handle-A1				
Document Feeder options:	Direct Print Kit (for PDF/XPS)-H1, Barcode Printing Kit D1, Data Erase Kit-C1, HDD Data Encryption & Mirroring Kit-C2, Encrypted Printing Software-D1, Secure Watermark-B1, Web Access Software-H1, Access Management System Kit-B1, Expansion Bus-F1, Wireless LAN Board-B1, IPsec Board-B2, 2.5"/80GB HDD-C1, 2.5"/250GB HDD-D1, REMOVABLE HDD KIT-AD1, Document Scan Lock Kit-A1				
EFI Options:	SeeSequence Compose, SeeSequence Impose, SeeSequence Suite, Removable HDD Kit-B4				
Send/Fax Options:	Universal Send Digital User Signature Kit-C1, Super G3 FAXBoard-AF1, Super G3 2nd Line Fax Board-AF1				
Paper Supply Options:	POD Deck Lite-A1, Tab Feeding Attachment Kit-B1				
Punch tools:	Punch Unit-BG1/BH1 (for Booklet Finisher-D1 or Staple Finisher-D1), Punch Unit-BC1/BD1 (for Staple Finisher-F1 Pro or Booklet Finisher-F1 Pro)				
Other Options:	Utility Tray-A1, Copy Card Reader Attachment-A2, Card Reader-C1, Remote Operators Software Kit-B1, Voice Guidance Kit-F1, Multimedia Reader/Writer-A1, Serial Interface Kit-K1, Copy Control Interface Kit-A1				
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.					
Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.					



Canon Inc.
canon.com

Canon Europe
canon-europe.com

English Edition
© Canon Europa N.V., 2011