



Océ
CS2424
CS2436
printer

Doar printezi!



General	
Descriere	Printer color pentru formate mari
Tehnologia	Thermal inkjet-dye
Viteza	Oce CS2424 : 30 sec/A1 Oce CS2436: 48 sec/A0
Timp de incalzire	Instant
Configurare	Printer
Hartia	1 rola plus hartie pretaiata
Tava de livrare	Tava de livrare integrata pozitionata in fata.
Certificari	Energy Star, TuV GS, CETECOM, CE, UL, cUL, CB, FCC class B, RoHS
Printer	
Rezolutia	1200x1200 dpi. Interpolata 2400x1200 dpi
Capacitate hartie	Pana la 150 m pe rola, maxim 1 rola
Latimea output-ului	Oce CS2424: 203mm - 610mm Oce CS2436: 203mm - 914mm
Lungimea output-ului	254mm - 18000mm (este posibil sa fie mai lunga dar influenteaza



EUROCOM S.A.

Distribuitor Océ Technologies B.V. in Romania
Union International Center, etaj 6, Str. Ion. Campineanu 11, Sector 1, Bucuresti
Tel: (021) 311.29.70; 311.30.26; 311.13.74; 311.31.25

Pagina 1 din 3

Bucuresti
Fax: (021) 312.76.74



Printing for Professionals

www.eurocom.ro

	marginile)
Grosimea hartiei	56g – 350g / m ²
Tipuri de hartie	Draft, standard, reciclata, color, cretata; hartie transparenta, hartie foto si film
Controller	
Tipul controller-ului	Embedded
Memorie	256 MB
Formate acceptate	Garo, HPGL/2, HPRTL
Formate acceptate via Océ Client Tools	HPGL, HPGL/2, DWF, DWG, TIFF, JPEG, etc
Moduri de printare, copiere, scanare	
Concurentialitatea job-urilor	Océ Client Tools, Windows printer driver, driver Apple Machintosh
Managementul job-ului	Managementul cozii de printare cu Garo status monitor
Accounting	Contorizare inclusa si optional via Océ Repro Desk Studio
Optionale	
Software	Océ ReproDesk Studio, Onyx CADPro, Onyx GraphicsPro
Network	
Suport OS	Windows 2000(32) / XP (32&64)/Vista(32&64)/Windows7(32&64)/, Macintosh OS X(32&64)/
Interfata standard	Modul Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Conector de transfer tip B4pin; Standard IEEE 802.3 10base-T IEEE 802.3u 100base-TX / Auto-Negotiation IEEE 802.3ab 1000base-T / Auto-Negotiation IEEE 802.3 x Full Duplex
Protocoale retea	Protocol IPX/SPX (Netware 4.2(J), 5.1(J),6.0(J),
Mediu	
Consum	Modul activ : 140 W/ Ready mode: 6W/ Sleep mode : 1 W
Cerinte electrice (V/Hz/A)	100V – 240 V, 56/60 Hz
Zgomot	Modul activ : 50Db (A)/ Ready mode : 35Db(A)
Dimensiuni	Océ CS2424: 99.7 cm / 87 cm / 106.2 cm Océ CS2436: 130.4 cm / 87 cm / 106.2 cm
Greutate	Océ CS2424: 43.4 kg - 53.7 kg Océ CS2436: 62.9 kg - 75.1 kg
Cerneala	Cerneala cu densitate mare pe baza de apa : 2x Negru: pigment, 3x Color +1 negru: dye)

Dimensiune cartus	130 ml
Altele	Caseta mentenanta; Cap de printare; Sustinator rola



EUROCOM S.A.

Distribuitor Océ Technologies B.V. in Romania
Union International Center, etaj 6, Str. Ion. Campineanu 11, Sector 1, Bucuresti
Tel: (021) 311.29.70; 311.30.26; 311.13.74; 311.31.25

Pagina 3 din 3

Fax: (021) 312.76.74

www.eurocom.ro



Printing for
Professionals