

Water
Oil
Solvent

Product Description Instant dry, glossy, FSC environmentally certified, photo proofing paper with a microporous ceramic coating for rapid ink absorption and excellent image sharpness.

Physical Properties

Weight	198 ± 7 g/m ²		L, a*,b* delta b	93,1 ± 0,5; - 0,4 ± 0,3;
Thickness	202 ± 6 µm			- 2,8 ± 0,5; 0,8 ± 0,8
Opacity	>89		Gloss (BYK)60°	50 ± 5 %
CIE Whiteness (D65/10°)	100			

Features/ Applications

Instant dry
Outstanding media colour consistency
Large color gamut
Excellent image sharpness
Smear resistant
Universal compatibility
FOGRA certified
FSC environmentally certified
Very consistent layflat

Posters, Points of sale/purchase
Indoor/Outdoor signage
Calendars
Layout Proofing

Available Widths (mm)

2"Core: 610 914 1067 1118 1270 1524 Refer for our current offering to www.mediaguide.oce.com.

Storage Conditions

Shelf life: 2 years
Temperature 15 - 25°C, Relative Humidity 30 - 70%. Repack opened rolls when not in use

Print Conditions

Best results are obtained at 23°C and 50% RH.
Higher humidity will increase drying time, low humidity may cause curling.

Printer Compatibility

Refer to www.mediaguide.oce.com

Environment, Health & Safety

No Material Safety Data Sheet required. Paper waste is not suitable for recycling.

Lamination Compatibility

Hot	Warm	Cold
1	3	3

3= excellent 2= fair 1= not recommended


Hot, heat activated 105°C -130°C
Warm, heat activated 85°C - 95°C
Cold, pressure sensitive

Outdoor Use

Not suitable for outdoor use. Short time outdoor use possible only when laminated.

Color Profiles

Océ develops high-quality colour profiles for media / ink / printer / RIP combinations. Check availability of profiles for your printer on the download section of www.mediaguide.oce.com.



Processing Guidelines



Printing guidelines

Allow material to adapt to room conditions for 24 hours before printing

Keep out of direct sunlight.

Side to be printed is the outer side of the roll.

Use of gloves is recommended

Recommended ink laydown max. 200%; use of composite black is not recommended When using Océ ICC Color profiles for this media, profiles will take care of ink limits and maximum image quality will be achieved.

Dye inks on microporous coated products can exhibit some fading (apart from UV) due to its open structure. Gasses like Ozone cause this phenomenon. Lamination will solve this issue.

Lamination guidelines

Immediate lamination possible.

One-sided lamination may cause curling.