

<b>Toner</b>
Oil
Solvent

## Product information

**Product Description** A quality paper with a low chlorine content and high whiteness. The perfect paper for external use where the quality of your documents must reflect the image of your work and organisation

## Physical Properties

<b>Grammage</b>	75 ± 3 g/m <sup>2</sup>	<b>Acidity</b>	PH 7,5 ± 1
<b>Thickness</b>	103 ± 3 µm	<b>Whiteness CIE</b>	159 ± 3
<b>ISO Brightness R457 +UV</b>	109 ± 1 %	<b>ISO Brightness R457 - UV</b>	88 ± 1 %
<b>Opacity</b>	92 ± 1 %	<b>Stiffness (Lorentzen MD)</b>	140 ± 20 mN
<b>Stiffness (Lorentzen CD)</b>	52 ± 10 mN	<b>Porosity</b>	820 ± 150 ml/min
<b>Roughness (Bendtsen) WS</b>	260 ± 50 ml/min	<b>Roughness (Bendtsen) TS</b>	280 ± 50 ml/min

## Storage Conditions

Best results are obtained between 20 ± 3°C and 50 ± 5 % RH.

## Available Widths (mm)

**3" core:** 210 297 420 594 620 625 650 841 880 914 [mediaguide.oce.com](http://mediaguide.oce.com).

## Environment, Health & Safety

No Material Safety Data Sheet required. Paper waste suitable for recycling.

## Printer Compatibility

Refer to [www.mediaguide.oce.com](http://www.mediaguide.oce.com)

## Lamination Compatibility

Hot	Warm	Cold	
1	1	3	Hot, heat activated: 105 °C – 130 °C
			Warm, heat activated: 85 °C – 95 °C
			Cold, pressure sensitive

3= excellent 2= fair 1= not recommended

## Outdoor Use

Designed for indoor use.

## Colour Profiles

Océ develops high-quality colour profiles for media / ink / toner/ printer / RIP combinations. Check availability of profiles for your printer on the download section of [www.mediaguide.oce.com](http://www.mediaguide.oce.com).

