All-in-one colour printer with business-in-box concept for all-round graphics applications

An all-rounder colour printer, the Océ ColorWave 700 is designed for wider graphic arts applications and offers high quality, instant dry and water-resistant prints on uncoated, thick and custom media.



All-rounder colour printer for professionals

- Versatile ENERGY STAR[®] qualified printer for wider graphics arts applications with capacity of up to 6 media rolls
- Ideal for reprographics, sign and display print providers and in-house printing applications
- Enhanced custom media capabilities that support media thickness up to 0.8 mm with Océ MediaSense technology
- Extensive print capabilities ranging from CAD drawings on plain paper to banners on Tyvek; from decorative prints on self-adhesive film to applications on canvas
- Virtually no dust or ozone emission

The next generation of CrystalPoint technology

- New media path design
- 4 colour Océ TonerPearl system
- Good adhesion properties, instant dry and waterresistant prints even on uncoated media

Ideal for multi-user environments

- Swift running with Intel[®] Core[™] i5 processor, dual hard drive and 8GB RAM
- Optional Adobe® PDF Print Engine 3 (APPE3) for accurate previews and fast processing speeds with end-to-end PDF workflows



Reduced need for servicing

- Océ PAINT technology repairs nozzle failures automatically, even on the fly, and extends the lifetime of the imaging device
- Fewer requirements for daily maintenance

Intuitive touch screen and easy accessibility

- Intuitive usability on Océ ClearConnect 10.6" touch screen with tablet-like gestures
- Preview, print, retrieve, create sets, zoom-in, zoomout, select rolls and print profiles, see toner levels and connect to 3rd party software applications

Secure and connected

- Print from and scan to your cloud server, mobile phone, tablet or USB drive
- Optional built-in user authentication features

Colour scanning

- · Optional built-in colour scanner
- Optimise scans with patented Océ Colour Image Logic[®] workflow
- High quality scans regardless of condition of original file
- Automatically clear background noise and capture details, even from mixed originals that include text, highlighted lines and photos





Technical Specifications

Océ ColorWave 700

General

Printer Description

Imaging technology

Print resolution Print modes Consumables Print speed

Media capacity Size (WxDxH) Weight Standard output option

Technology Océ MediaSense

Océ POWERsvnc

Océ PAINT

Océ ImageLogic

Controller

Controller Processor Memory Video card Hard disk Interface

Page description language

Printing protocol Back channel protocol Security

Cloud support

Media handling

Supported types of media rolls Media thickness Maximum media length Media width Media weight Media cutting Supported media types

Scanner

Description Technology

Scan resolution Scan speed Original width

All-rounder colour printer designed for wider graphic arts applications, high quality, instant dry and waterproof prints on uncoated, thick and custom media [max 750 characters] Océ CrystalPoint Technology brings instant-dry, water-resistant prints even on uncoated media

600 x 600 dpi 9 different quality modes and Océ Print assistant (OPA) [1] 4 colour TonerPearl system; Cyan, Magenta, Yellow and Black B&W: 225 A1/h, Colour: 212 A1/h or up to 247 m²/h mechanical printing speed $^{\rm [2]}$ 4 - 6 rolls in 2 - 3 drawers 2100 mm x 900 mm x 1580 mm 290 kg [3]

Top Delivery Tray (Capacity up to 75 sheets)

Automatically adjusting the height of imaging device from media according to media thickness The architecture that combines controller. Adobe* PDF Print Engine 3 (APPE3), fast processor and high capacity RAM (Piezo Acoustic Integrated Nozzle Technology) Automatically repairing nozzle failure even on the go

Patented optimisation process for copying and scanning

Windows* 8 (64-bit) embedded controller Intel[®] Core[™] i5 8 GB RAM Intel[®] HD Graphics, 1GHz 2 x 500 GB Ethernet 100 Mbits/s, 1 Gbit/s, TCP/IP: DHCP,IPv4, IPv6, https, Discovery: WSD, LPD, NetBios TIFF 6.0, JPEG1.02, HPGL, HPGL2, C4, Calcomp 906/907/951, CALS 1, NIRS, NIFF, PS3/PDF1.7/APPE3 (optional) LPR, LPR to DRP, FTP, WebDAV, Collaborate, WSD print SNMP printer MIB, Océ Wave interface 1.3, WSD, OCI E-shredding, IPsec, HTTPS, extended security protection for administrator, audit logging, User authentication on local UI for FTP, SMB and WebDAV; Configurable HTTPS Certificates,

(optional) Unlimited user authentication on cloud via WebDAV or a third party provider such as Microsoft SharePoint*, Dropbox*, Boo com, box.net, Google Drive™, Microsoft SkyDrive*, Amazon*, Cloud Safe*, My Disk*

Removable Hard Drives (optional), Access Management

Max. roll diameter: 180 mm; Max. roll weight: 20 kg; Media loose on core

0.8 mm (30 mil); Film: 0.065 - 0.2 mm (2.5 - 8 mil) 200 m (656 feet)

297 mm - 1067 mm (11" - 42"): Automatic width detection Paper: 60-200 g/m2 (16-53 lbs)

Automatic, manual or off

Uncoated papers, uncoated Tyvek, self-adhesive papers, self-adhesive coated vinyl, blue back papers, textile types, polypropylene films, polyester films, light blocks films, canve soft banner, instant dry photo paper, coated & uncoated non woven wall paper (fleece), backlit paper, self-adhesive wall paper, several natural and synthetic textiles

Built-in Océ Scanner Express II (Optional)

Colour Contact Image Sensor (CIS) scanner works based on Océ Image Logic technology 600 x 600 dpi

14.6 m/min (Black&White); 4.8 m/min (Colour)

208 - 914 mm (8.2 - 36"); Automatic width detection

Original length Original thickness Zoom Scan formats

Scanning destinations

Scan protocol Naming Size scanner (WxDxH)

Weight scanner **User Interface**

Description

Screen size Resolution Number of colours Technology Operation

Features

Environmental Specifications (Printer)

Sound pressure level Sound power level Ozone concentration Heat emission Power requirements Power consumption Environmental labels Recycling

Workflow Drivers

Job submission tools

Océ ClearConnect touch screen

Options Hardware

Software

208 - 16000 mm (8.2 - 630") [4] Up to 0.8 mm (0.03") [! 10 - 1000 % TIFF, PDF, PDF/A, JPEG, CALS, multi-page PDF, multi-page PDF/A and multi-page TIFF USB drive, FTP, SMB, controller, mobile device via Océ Mobile WebTools, WebDAV Cloud, Collaborate FTP, SMB, Scanning to cloud Naming scanned files on Océ ClearConnect touch panel 1097 mm x 308 mm x 140 mm (43 x 12 x 5.5") 25 kg

Océ ClearConnect multi-touch user panel 10.4" 800 x 600 pixels 16.2 Million Projective capacitive touch screen 3 buttons for [Wake-up], [Stop, interrupt, abort] and [Home]; Multi-touch tablet like gestures Custom positioning (Tilt from -4° to +45° and turn from -45° to +180°); Operation status light (red, green)

Ready: 36 dB(A): Active: 57 dB(A) Ready: 4.7 B(A); Active: 6.9 B(A) 0 mg/m3 Ready: 214 W, Active: 395 W 100 - 240 V. 50 - 60 Hz Sleep: 2.5 W: Ready: 199 W: Active: 380 W CE, TÜV GS, CETECOM, c-UL-US, RCM, ENERGY STAR*, FEMP

Printer is made of steel and highly recyclable plastics; minimum 86% of the engine can either be upcycled or recycled. The packaging for toner cartridge can be reused as maintenance cassette and is made of recyclable plastic. Good deink ability of prints.

Océ Wide Format Printer Driver 2 for Microsoft Windows^{*}, Océ PostScript^{*} 3 driver

Dock Wide Format Printer Driver2 for Windows^{*}, Océ PostScript^{*} 3 driver, external locations (SMB, FTP, LPR, WebDAV), Mobile devices via Océ Express WebTools ⁽⁶⁾, Océ Publisher Select 2, Océ Publisher Mobile, USB flash drive, Cloud services. Supported by Adobe^{*} PostScript 3, Adobe^{*} PDF Print Engine 3 (APPE 3) and Onyx software.

Jobs can be queued in the Smart Inbox. They can be viewed, edited, deleted, sent, saved and resubmitted on the panel. The software settings can be changed on Océ Express WebTools. You can view printer status and access the online help docume in many languages and manage 3rd party applications. document

Océ Scanner Express II, Additional roll drawer, EsTe 4311 full fold series, EsTe 2400 fanfold, Océ Delivery Tray (Capacity up to 150 sheets), Take-Up Module, Receiving rack

Océ Account Centre, Océ View Station, Access Management ⁽⁷⁾ Onyx, Adobe[®] PostScript[®] 3, Adobe[®] PDF Print Engine 3 (APPE 3), Administrative Logon, 3rd Party Enabler, App+ Enabler

FOOTNOTES [1] Océ Print Assistant is a tool that determines the best print mode automatically based on file

content [2] Measurements are based on printing CAD file at high-speed print profile

- [2] Measurements are based on printing CAU file at high-speed print prome
 [3] For 1 printer and 1 drawer
 [4] Depending on the file type
 [5] For non-rigid media only
 [6] Océ Express WebTools enables you to manage the device remotely on the web
 [7] Access Management is a user authentication tool that enables users to access the printer by entering user credentials on the ClearConnect touch screen or swiping cards if there is connected card reader. Authorization is managed by using Active Directory.



Canon Inc. canon.com Canon Europe canon-europe.com English edition © Canon Europa N.V.,2015

