iPF770

Large Format Print Solutions ideal for CAD & GIS

The imagePROGRAF iPF770 is a 36"/A0 printers, delivering class leading productivity, exceptional quality, accuracy and an advanced set of features to ensure an excellent return on investment.







Key features:

- High-volume continuous printing, with 130 ml hot-swap ink tanks that can be replaced while the unit is printing
- A0 output in Fast Economy mode in 48 seconds
- Space saving Unique compact design to fit anywhere
- Highly accurate with 0.02 mm minimum line width and +/-0.1 % line accuracy
- 5-colour dye-and-pigment ink system with new magenta ink for reproduction of brighter red colour
- Printing PDF / TIFF / JPEG / HP-GL2 easily, from general graphics to CAD and GIS drawings, with bundled Direct Print & Share Utility
- Cloud ready for immediate sharing, with easy access even from mobile devices
- Use the bundled PosterArtist Lite software and Print Plug-in for Microsoft Office to create powerful large format posters with ease
- Manage costs and track ROI with full accounting tools

iPF770

36 INCH

2,400 X 1,200 DPI

130 ML INK TANKS

ECONOMY PRINTING MODE

5 COLOUR WITH NEW MAGENTA

A0 48 SECONDS

15,360 NOZZLES

BORDERLESS PRINTING



iPF770

TECHNOLOGY

Printer Type

Print Technology

Number of Nozzles

Print Resolution Nozzle Pitch Guaranteed Minimum Line Width

Line Accuracy Ink Droplet Size Ink Capacity

Ink Type

OS Compatibility

Printer Languages

Standard Interfaces

PRINTING SPEED

AO Size, Plain Paper

AO Size, Coated Paper

MEMORY **Buffer RAM**

Media Width

Media Thickness Minimum Printable

Maximum Printable Length

Maximum Media Roll Diameter

5 Colour - 36" / 914.4 mm

Canon inkjet on Demand 6 colours integrated type (6 chips per print head x 1 print head)

Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each

2,400 x 1,200 dpi 1,200 dpi x 2 0.02 mm

±0.1% or less 4 Picoliter per colour Bundled Starter Ink: 90 ml Sales Ink: 130 ml

Dye / Pigment Reactive Ink Dye: Cyan, Magenta, Yellow, Black Pigment: Matte Black

32 bit - Windows XP, Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows Server 2003 / 2003R2, Windows Server 2008 64 bit - Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows Server 2003 / 2003R2, Windows Server 2008 / 2008R2, Windows Server 2012 / 2012R2
Mac: OSX - 10.6.8 - 10.10.x

GARO (Graphic Arts Language with Raster Operations), HP-GL/2, HP RTL

USB 2.0 High-Speed Ethernet 10 / 100 / 1000 Base-T/TX

0:48 min (Fast Economy Mode)

0:48 min (Fast Mode) 1:15 min (Standard Mode) 1:15 min (Fast Mode) 2:24 min (Standard Mode) 3:50 min (High Quality Mode)

PAPER HANDLING

Roll Paper: 10" / 254 mm - 36" / 914.4 mm Cut Sheet: 8" / 203.2 mm - 36" / 914.4 mm Roll Unit: 0.07 - 0.8 mm

Top Loading Manual Feed: 0.07 - 0.8 mm

Roll: 203.2 mm Cut Sheet: 279.4 mm

18 m (Varies according to the OS and application)

Paper Feed Method

Borderless Printing Width (Roll Only)

DIMENSIONS AND

Physical Dimensions (W x D x H)

Weiaht

Software Included

POWER AND OPERATING

REQUIREMENTS Power Supply Power Consumption

Operating Environment

Noise Level (Approx.)

Regulations

WHAT'S INCLUDED

What's In The Box?

OPTIONS

Roll Holder Set CONSUMABLES

Ink Tanks

Maintenance Cartridge

Roll Feed: One Roll, Top Loading, Front Output Top Loading Manual Feed: One Sheet, Front Output

10" (254 mm), B4 (257 mm), A3 (297 mm), Banner (300 mm), 14" (356 mm), A2 (420 mm), A2+/17" (432 mm), B2 (515 mm), A1 (594 mm), 24" (610 mm), B1 (728 mm), A0 (841 mm), 36" (914 mm)

1.304 (W) x 887 (D) x 1.062 (H) mm (With basket open) 1,304 (W) x 1,100 (D) x 1,062 (H) mm (When basket is at the extended position for flatbed stacking)

64.6 kg (roll holder included, no inks, no print heads)

Canon Printer Driver, Status Monitor / Print Monitor, Printer Driver ExtraKit - Free Layout and iR enlargement Copy, Printer Driver Optimization Module for AutoCAD, Media Configuration Tool, PosterArtist Lite (PC only), Print Plug-in for Microsoft® Office (PC only), Direct Print & Share, Custom Installer Creation Tool

AC 100 - 240 V (50 - 60 Hz)

Operation: 140 W or less

Power Off Standby: 0.5 W or less 15 - 30°C, 10 - 80 % (Condensation free)

Operation: approx. 48 dB Standby: 35 dB or less Accoustic Power: 6.5 Bels

Based on ISO 7779 Europe: CE mark.

Germany: TUV mark, Russia: EAC Other Countries: CB Certification

ENERGY STAR, RoHS (EU), WEEE (EU), ErP Directive (Lot6, 26), China RoHS, Chemical Substances Regulation, Battery certification (EU, Japan, USA, China, Taiwan), Packing material Regulation (EU, USA, Korea)

1 print head, 1 set of starter ink tanks (C, M, Y, BK, 2 x MBK - 90 ml), 3 inch core adapters, set up guide, User software CD-ROM (Mac & Win), Carrying caution leaflet, Safety / Standard Environment leaflet, PosterArtist Lite leaflet, PosterArtist Lite software CD-ROM, Announcement of LFP Survey Program, EAC leaflet, Quick guide

RH2-33

PFI-107: 130 ml - C, M, Y, BK, 2 x MBK

MC-10

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/ or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

Canon Inc. canon.com Canon Europe canon-europe.com English edition © Canon Europa N.V.,2014 Canon (UK) Ltd Woodhatch Reigate Surrey RH2 8BF Telephone no 01737 220000 Facsimile 01737 220022 canon.co.uk

Canon Ireland 3006 Lake Drive Citywest, Saggart Co.Dublin, Ireland Telephone No: 01 2052400 Facsimile No: 01 2052525 canon.ie

imagePROGRAF



PosterArtist